15W Triple Output Switching Power Supply

Features:

- AC input 176-264V only
- Miniature
- Protections:SCP/ OLP/ OVP
- High reliablity, Low cost
- 100% full load burn-in test

Input Volt. & Freq. ……176~264VAC/47~63Hz
Inrush Current……50A@230VAC (cold start)
DC adjustment range …… ±10% (rated output voltage)
Overload protection ……110%~150% (rated load), Auto-recovery
Over voltage protection……115%~135% (rated output voltage)
Short circuit protection…… Long-term
Setup time …… ≤1S@230VAC
Hold-up time …… ≥20mS@230VAC
Withstand voltage……Input-Output: AC1500V, 1min
Input-Ground: AC1500V, 1min
Output-Ground: DC500V, 1min
Operating ambient ……0~45℃,20%~90%RH (Non condensing)
Safety standards……EN60950,GB4943
Dimension (L*W*H) ……108X46X30mm

Model No.	DC Output		Tol.	R&N	Effi.
MGZ-H15T5+4-24	5V	0. 5A	±5%	≤50mV	65%
	4V	0. 5A	±6%	≤50mV	
	-24V	0. 25A	±6%	≤240mV	
MGZ-H15T5±12	5V	1. 5A	±5%	≤50mV	71%
	12V	0. 3A	±7%	≤120mV	
	-12V	0. 3A	±7%	≤120mV	
MGZ-H15T5±15	5V	1.5A	±5%	≤50mV	65%
	15V	0. 3A	±10%	≤150mV	
	-15V	0. 3A	±10%	≤150mV	
MGZ-H15T±5+12-5	5V	1.5A	±1%	≤50mV	60%
	-5V	0. 3A	±10%	≤50mV	
	12V	0. 3A	±5%	≤120mV	
MGZ-H15T5-5-24R	5V	1.6A	±5%	≤50mV	66%
	-5V	0. 4A	±10%	≤50mV	
	-24V	0. 05A	±10%	≤240mV	