

## 40W Dual Output Switching Power Supply



### Features:

- AC input 176-264V only
- Miniature
- Protections: SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

Input Volt. & Freq. ....	176~264VAC/47~63Hz
Inrush Current.....	50A@230VAC (cold start)
DC adjustment range .....	±10% (rated output voltage)
Overload protection .....	105%~135% (rated load), Auto-recovery
Setup time .....	≤1S@230VAC
Hold-up time .....	≥20mS@230VAC
Withstand voltage.....	Input-Output: AC1500V, 1min
	Input-Ground: AC1500V, 1min
	Output-Ground: DC500V, 1min
Operating ambient .....	0~45°C, 20%~90%RH (Non condensing)
Safety standards.....	EN60950, GB4943
Dimension (L*W*H) .....	127X76X30mm

Model No.	DC Output	Tol.	R&N	Effi.
MGZ-H40D5+24	5V 2.2A	±3%	≤50mV	75%
	24V 1A	±10%	≤240mV	
MGZ-H40D5+12	5V 3A	±3%	≤50mV	75%
	12V 2A	±10%	≤120mV	
MGZ-H40D3.3+5	3.3V 5A	±3%	≤50mV	75%
	5V 5A	±10%	≤50mV	