50W Triple Output Switching Power Supply

CASE: P52-6

Features:

- Normal Size
- AC input 176-264V only
- Protections:SCP/ OLP/ OVP
- High reliablity, Low cost
- 100% full load burn-in test

Input Volt. & Freq. ·····176~264VAC/47~63Hz
Inrush Current·····40A@230VAC (cold start)
DC adjustment range ····· ±10% (rated output voltage)
Overload protection ·····105%~150% (rated load), Auto-recovery
Over voltage protection·····115%~135% (rated output voltage)
Short circuit protection····· Long-term
Setup time ····· ≤1S@230VAC
Hold-up time ····· ≥20mS@230VAC
Withstand voltage·····Input-Output: AC1500V, 1min
Input-Ground: AC1500V, 1min
Output-Ground: DC500V, 1min
Operating ambient·····0~45℃,20%~90%RH (Non condensing)
Safety standards·····EN60950,GB4943
Dimension (L*W*H) ·····160X98X38 mm

Model No.	DC Output		Tol.	R&N	Effi.
GZT-H50T5+12R-5R	5V	6A	±3%	≤50mV	72%
	12V	1A	±3%	≤120mV	
	-5V	1A	±3%	≤50mV	
GZT-H50T5+12R-12R	5V	5A	±3%	≤50mV	72%
	12V	1A	±3%	≤120mV	
	-12V	1A	±3%	≤120mV	
GZT-H50T5+15R-15R	5V	4A	±3%	≤50mV	70%
	15V	1A	±3%	≤150mV	
	-15V	1A	±3%	≤150mV	