

60W Single Output Switching Power Supply



CASE : P52-5

Features:

- Miniature
- AC input 176-264V only
- Protections: SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

Input Volt. & Freq.	176~264VAC/47~63Hz
Inrush Current.....	50A@230VAC (cold start)
DC adjustment range	± 10% (rated output voltage)
Overload protection	105%~150% (rated load), Auto-recovery
Over voltage protection.....	115%~135% (rated output voltage)
Short circuit protection.....	Long-term
Setup time	≤ 1S@230VAC
Hold-up time	≥ 20mS@230VAC
Withstand voltage.....	Input-Output: AC1500V, 1m in Input-Ground: AC1500V, 1m in Output-Ground: DC500V, 1m in
Operating ambient.....	0~45°C, 20%~90%RH (Non condensing)
Safety standards.....	EN60950, GB4943
Dimension (L*W*H)	129X98X38 mm

Model No.	DC Output		Tol.	R&N	Effi.
GSM-H60S12	12V	5A	±3%	≤ 120mV	80%
GSM-H60S15	15V	4A	±3%	≤ 150mV	80%
GSM-H60S24	24V	2.5A	±3%	≤ 240mV	82%