

60W Dual Output Switching Power Supply



Features:

- AC input 176-264V only
- Miniature
- Protections: SCP/ OLP/ OVP
- High reliability, Low cost
- 100% full load burn-in test

Input Volt. & Freq.	176~264VAC/47~63Hz
Inrush Current.....	40A@230VAC (cold start)
DC adjustment range	±10% (rated output voltage)
Overload protection	130%~150% (rated load), Auto-recovery
Over voltage protection.....	105%~135% (rated output voltage)
Short circuit protection.....	Long-term
Setup time	≤1.5S@230VAC
Hold-up time	≥20mS@230VAC
Withstand voltage.....	Input-Output: AC3000V, 1min
	Input-Ground: AC1500V, 1min
	Output-Ground: DC500V, 1min
Operating ambient	0~45°C, 20%~90%RH (Non condensing)
Safety standards.....	EN60950, GB4943
Dimension (L*W*H)	127X76X40 mm

Model No.	DC Output		Tol.	R&N	Effi.
MGZ-H60D3.3+12	3.3V	10A	≤±7%	≤50mV	68%
	12V	1A	≤±10%	≤120mV	
MGZ-H60D5+12	5V	10A	≤±5%	≤500mV	75%
	12V	1A	≤±10%	≤120mV	
KHD-H60D5+24NC	5V	3A	≤±3%	≤50mV	73%
	24V	2A	≤±10%	≤240mV	